














Dati Tecnici - Specifications

											
	cond	comp. W	ABS. W	Fuse	Kwh/100Kg	l / h	kg	Lbs	kg	Lbs	Ton CO2 equiv.
M502 A		6274	2550	20	13.47	20.2	98	216	116	256	6,28
M502 W		-	-	-	-	-	-	-	-	-	-



Produzione Ghiaccio - Ice Production

Raffreddamento ad aria - Air Cooled Unit



Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	415	440	453	465
50°	915	970	999	1025
21°	385	410	425	431
70°	849	904	936	950
32°	307	341	353	364
90°	677	752	778	802
38°	276	307	316	326
100°	608	677	696	719

Raffreddamento ad acqua - Water Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°				
50°				
21°				
70°				
32°				
90°				
38°				
100°				



PANNELLO DI CONTROLLO - CONTROL PANEL

	Alimentazione Powered
	In Funzionamento Operating
	Deposito Pieno/Lavaggio Storage Full / Washing
	Allarme Alarm
	Allarme Alta Pressione High Pressure Alarm
	Pulsante Reset/Lavaggio Button Reset/Washing




DIMENSIONI - DIMENSIONS

LxPxH(mm): 760 x 620 x 725
WxDxH(in):2915/16"x247/16"x289/16"

DEPOSITO - SLOPE BIN

D205 - D255 - D305 (KM305)
D405 KFM404) - D505 (KFM505)

TIPO GHIACCIO - ICE TYPE

	HALF-LARGE 10 x 29 x 24 - 6 gr 555 PZ. / CICLO PCS / CYCLE
	DICE 22 x 22 x 24 - 10 gr 342 PZ. / CICLO PCS / CYCLE
	LARGE 29 x 29 x 24 - 17 gr 210 PZ. / CICLO PCS / CYCLE

CONDIZIONI USO-OPERATING REQUIREMENTS




220-240V / 1 / 50HZ R404A GWP=3922


MIN	MAX
10°C (50°F)	40°C (104°F)
5°C (41°F)	35°C (95°F)
- 10 %	+ 10 %
1 BAR (14 PSI)	5 BAR (70 PSI)

Calore espulso - Rejected Heat **6581 W**
Volume aria - Air Volume **1180 m³/h**


Vista frontale
Front view




Vista laterale
Lateral view



Vista superiore
Top view




AIR COOLED 




Back View

WATER COOLED 



Back View



- A** Water drain Ø20 mm
- B** Potable water inlet 3/4 GAS
- C** Electrical cable supply
- D** Water cooled inlet 3/4 GAS
- E** Water cooled outlet 3/4 GAS